


# Schedule of Accreditation

issued by

## United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

 <b>2654</b>  Accredited to <b>ISO/IEC 17025:2017</b>	<b>Horiba MIRA Limited</b>	
	<b>Issue No: 024    Issue date: 06 May 2021</b>	
	<b>Unit 1</b> <b>Quatro Park</b> <b>Paycocke Road</b> <b>Basildon</b> <b>Essex</b> <b>SS14 3GH</b>	<b>Contact: Mr Dean Rattenbury</b> <b>Tel: +44 (0) 1268 290108</b> <b>Fax: +44 (0)1268 290123</b> <b>E-Mail: dean.rattenbury@horiba-mira.com</b> <b>Website: www.horiba-mira.com</b>
<b>Testing performed at the above address only</b>		

### Flexible Scope

The Flexible Scope applies to the laboratory's accreditation to ISO/IEC17025:2017 for testing activities in accordance with the standards listed in the schedule. This may also include tests on the same or similar product types against standards, or customer-specified methods, that are not specifically listed in this Schedule, providing that:

1. The method or standard does not introduce new principles of measurement.
2. The method or standard does not require measurements to be made outside the parametric boundaries defined in this Schedule.

Information about flexible scopes of accreditation is available in UKAS document GEN 4.



2654

Accredited to  
ISO/IEC 17025:2017

**Schedule of Accreditation**  
issued by  
**United Kingdom Accreditation Service**  
2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

**Horiba MIRA Limited**

**Issue No: 024 Issue date: 06 May 2021**

Testing performed at main address only

DETAIL OF ACCREDITATION

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
VEHICLES IN EEC & ECE CATEGORIES M1, M2, M3 N1, N2, N3		
AEROSPACE COMPONENTS AND EQUIPMENT	ENVIRONMENTAL TESTING	Documented In-House Methods, Customer Procedures and International Standards
AGRICULTURE EQUIPMENT		
AUTOMOTIVE COMPONENTS AND ASSEMBLIES	HIGH TEMPERATURE (Constant)	IEC 60068-2-2 :2007 BS EN 60068-2-2 :2007 GME 5034 (Sun Blinds) GME 01124 GME 01125 GME 01143
COMPUTER AND PERIPHERAL EQUIPMENT	Max temp: +120 °C Limiting chamber size: 3.0 m x 3.0 m x 3.0 m	RTCA DO160G Section 4 MIL-STD-810G, Method 501.5 DEF STAN 00-35, Part 3, Issue 4, Test CL2, (superseded)
CONSTRUCTION PLANT	Max temp: +90 °C	
EQUIPMENT	Limiting chamber size: 4.0 m x 3.0 m x 3.0 m	
DOMESTIC APPLIANCES AND COMPONENTS	LOW TEMPERATURE (Constant)	IEC 60068-2-1 :2007 GME 5034 (Sun Blinds) GME 01124 GME 01125 GME 01143
ELECTRICAL/ELECTRONIC COMPONENTS	Min temp: - 70 °C Limiting chamber size: 1.0 m x 1.0 m x 1.0 m	RTCA DO160G Section 4 MIL-STD-810G, Method 501.5 DEF STAN 00-35, Part 3, Issue 4, Test CL5, (superseded)
MARINE EQUIPMENT		
MINING PLANT AND EQUIPMENT	Min temp: - 45 °C Limiting chamber size: 3.0 m x 3.0 m x 3.0 m	
PLASTIC COMPONENTS		
RECORDING/INDICATING EQUIPMENT	Min temp: - 40 °C Limiting chamber size: 4.0 m x 3.0 m x 3.0 m	
TELECOMMUNICATION EQUIPMENT		



2654

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Horiba MIRA Limited

Issue No: 024 Issue date: 06 May 2021

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
As Listed on Page 2	<p>ENVIRONMENTAL TESTING (cont'd)</p> <p>HIGH/LOW TEMPERATURE, WITHOUT HUMIDITY (Cyclic)</p> <p>Max temp: + 120 °C Min temp: - 45 °C Limiting chamber size: 3.0 m x 3.0 m x 3.0 m</p> <p>HIGH/LOW TEMPERATURE CYCLING WITH HUMIDITY (Cyclic)</p> <p>Max temp: + 85°C with humidity. +120°C (uncontrolled humidity) Min temp: - 45 °C (uncontrolled humidity) Humidity range: 40 %RH - 95 %RH Limiting chamber size: 3.0 m x 3.0 m x 3.0 m</p> <p>Max temp: + 85 °C Min temp: - 40 °C (uncontrolled humidity) Humidity range: 40 %RH - 80 %RH Limiting chamber size: 4.0 m x 3.0 m x 3.0 m</p> <p>HIGH HUMIDITY - STEADY STATE</p> <p>Max temp: + 85°C Min temp: - 45 °C Uncontrolled humidity Humidity range: 40 %RH - 95 %RH Limiting chamber size: 3.0 m x 3.0 m x 3.0 m</p> <p>Max temp: + 85 °C Min temp: - 40 °C (Uncontrolled humidity) Humidity range: 40 %RH - 80 %RH Limiting chamber size: 4.0 m x 3.0 m x 3.0 m</p>	<p>IEC 60068-2-14:2009, Test Ng BS EN 60068-2-14:2009, Test Ng</p> <p>IEC 60068-2-38:2009 BS EN 60068-2-38:2009 GMW 14109 GMW 14113 (draft) DEF STAN 00-35, Part 3, Issue 4:2006, Test CL6, (superseded) RTCA DO160 G section 4. IEC / BS EN 60068-2-30:2005 MIL STD 810G Method 507.5 (superseded)</p> <p>BS EN 60068-2-78:2001, TestCab BS EN 60068-2-78:2013 TestCab MIL-STD-810G, Method 507.5 DEF STAN 00-35, Part 3, Issue 4, Test CL6, (superseded)</p>



2654

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

#### Horiba MIRA Limited

Issue No: 024 Issue date: 06 May 2021

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
As listed on Page 2	<p><b>THERMAL SHOCK</b> (Automatic Transfer)</p> <p>Max temp: + 135 °C Min temp: - 45 °C Limiting chamber size: 770 mm x 610 mm x 650 mm</p> <p><b>VIBRATION</b> Sinusoidal and Random EM Vibrators Ambient and Climatic</p> <p>Peakthrust: 54.5 kN Frequency range: 5 Hz to 2.0 kHz Axes: Vertical and horizontal</p> <p>Climatic Vibration:</p> <p>Max temp: + 135 °C Min temp: - 60 °C Limiting chamber size: 1.0 m x 1.0 m x 1.0 m</p> <p>Max temp: + 135 °C Min temp: - 45 °C Humidity range: 40 %RH - 95 %RH Limiting chamber size: 3.0 m x 3.0 m x 3.0 m</p> <p>Max temp: + 90 °C Min temp: - 40 °C Humidity range: 40 %RH - 80 %RH Limiting chamber size: 4.0 m x 3.0 m x 3.0 m</p> <p><b>TEMPERATURE / HUMIDITY / LOW PRESSURE (Altitude)</b></p>	<p>IEC 60068-2-14:2009, Test Na BS EN 60068-2-14:2009, Test Na</p> <p>Sinusoidal</p> <p>IEC 60068-2-6:2008, Test Fc BS EN 60068-2-6:2008, Test Fc Mil Std 810G, method 514.6, Procedure 1 (superseded) DEF STAN 00-35, Part 3, issue 4, Test M1 RTCA DO160F, section 8</p> <p>Random</p> <p>IEC 60068-2-64:2008 BS EN 60068-2-64:2008 GMW 7293 Mil Std 810G, method 514.6, Procedure 1, (superseded) DEF STAN 00-35, Part 3, issue 4, Test M1 (superseded) RTCA DO160F, section 8</p> <p>Sine on Random Random on Random</p> <p>Mil Std 810G, method 514.6, Procedure 1, (superseded) DEF STAN 00-35, Part 3, issue 4, Test M1, (superseded) RTCA DO160F, section 8</p> <p>MIL-STD-810G, Method 520.3 MIL-STD-810G, Method 500.5 procedures I &amp; II only</p>



2654

Accredited to  
ISO/IEC 17025:2017

## Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Horiba MIRA Limited

Issue No: 024 Issue date: 06 May 2021

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
As listed on Page 2	<p>Temperature: -60°C to +100°C Humidity: 30% to 95%RH Pressure (Altitude): 8.4 mbar (100000 feet)</p> <p><b>MECHANICAL SHOCK</b></p> <p>Vibration systems Peak thrust : 54.5 kN Max accel : 50g Max displacement : 51mm p/p</p> <p><b>FREE FALL DROP</b> (rough handling) Concrete or Plywood surface Max Ht: 2 m Max item mass: 200 kg</p> <p><b>DUST INGRESS PROTECTION</b></p> <p>Limiting chamber size: 1.0 m x 1.0 m x 1.0 m</p>	<p>DEF STAN 00-35, Part 3, Issue 4, Test CL11 (procedure A), CL12 &amp; CL13, (superseded) IEC 60068-2-39:1976, Test M IEC 60068-2-40:1976, Test M IEC 60068-2-41:1976, Test M EN 60068-2-13:1999, Part 2, Test M</p> <p>IEC 60068-2-27:2009 BS EN 60068-2-27:2009</p> <p>BS EN 60068-2-31:2008 BS EN 60068-2-32:1993 (withdrawn) DEF STAN 00-35, Part 3, Issue 4, Test M4 &amp; M5, (superseded) MIL-STD-810G, Method 516.6 procedures IV &amp; VI only</p> <p>SAE J575 SAE J1211:1978 (Alternate Method) BS ISO 20653:2006 IP5Kk, IP6Kk BS EN 60529:1992 IP5X Cat2 &amp; IP6X Cat 2 DIN 40050-9 IP5Kk, IP6Kk</p>



2654

Accredited to  
ISO/IEC 17025:2017

### Schedule of Accreditation

issued by

### United Kingdom Accreditation Service

2 Pine Trees, Chertsey Lane, Staines-upon-Thames, TW18 3HR, UK

### Horiba MIRA Limited

Issue No: 024 Issue date: 06 May 2021

Testing performed at main address only

Materials/Products tested	Type of test/Properties measured/Range of measurement	Standard specifications/ Equipment/Techniques used
As listed on Page 2	<b>DIMENSIONAL MEASUREMENTS</b>  Angle: 0° to 90° Length: up to 1 m	In-House Procedures Customer Procedures
Automotive Electronic Components	<b>MECHANICAL CYCLING</b>  Pneumatic actuators Max stroke: 320 mm Max static thrust: 25 kN  <u>Associated Functional Exercising</u>  Automotive Components and Assemblies using In-House Test Equipment  Voltage DC: 10 mV to 65V Current DC: 30 mA to 10 A Resistance: 0.1 Ω to 10 MΩ Frequency: up to 1 MHz Time: 20 μs to 10 days	FORD CEPT 00.00-L-412    Documented In-House Methods and Customer Specifications
Assemblies and Components	Force application and measurement 0 N to 500 N	In-House Procedure GE3039/0/01 and Customer Specifications
END		